Kegel- und Entgratsenker HSS mit Querloch
Countersinks HSS with cross hole



Code **1720**



Code **1721**

BC NORM | HSS G | 90° | Z1 | CBN | TiN

Code	P			M		K				N				S
	1.1 – 2.1	3.1 – 4.1	5.1	1.1 – 2.1	3.1 – 4.1	1.1 – 1.2	2.1 – 2.2	3.1 – 3.2	4.1 – 4.2	1.1 – 1.5	2.1	2.2 – 2.3	4.1 – 4.2	1.1 – 1.2
1720	●					○	○		○	●	●	○	●	
1721	●	○		○		○	○		○		●		●	○

Querlochsenker aus HSS mit einer Schneide. Die Späne werden durch die Bohrung in Schaftrichtung abgeführt. Zum grat- und ratterfreien Entgraten, Ansenken und Versenken in gut zerspanbaren Werkstoffen wie allgemeinen Baustählen, NE-Metallen und Gusseisen. Geringe Schnittgeschwindigkeit sorgt für optimale Ergebnisse.

Cross hole countersink made of HSS with one cutting edge. The chips are removed through the hole in the direction of the shank. For burr and chatter-free deburring and countersinking in good machinable materials such as general structural steels, non-ferrous metals and cast iron. Low cutting speed ensures the best results.

Größe Size	Ø d1 mm	Ø d2 mm	L 1 mm		Artikel-Nr. Part-No.	TiN Artikel-Nr. Part-No.
1	2 – 5	6	45	1	1720 03 00001	1721 03 00001
2	5 – 10	8	48	1	1720 03 00002	1721 03 00002
3	10 – 15	10	65	1	1720 03 00003	1721 03 00003
4	15 – 20	12	85	1	1720 03 00004	1721 03 00004
5	20 – 25	12	102	1	1720 03 00005	1721 03 00005
6	25 – 30	15	115	1	1720 03 00006	-

BC ABS-Box / BC ABS-Box

Bezeichnung Description	Teile Pieces	Inhalt Content	Artikel-Nr. Part-No.
QS 4-K	4	Größe / Size: 1 · 2 · 3 · 4 Bereich / Range: Ø 2-5 · 5-10 · 10-15 · 15-20 mm	1720 13 30004



QS 4-K

Preisliste Seite / Price list page 80